

Power Supply Docking Station

AS0160-HR-160



- ◆ Low SWaP Design
- ◆ No assembly or training required
- ◆ Rapid installation in fixed and semi-fixed environments
- ◆ Integrated Speaker
- ◆ Uninterrupted AC/DC Switchover

GENERAL

PTS Part No	AS0160-HR-160
Description	Harris 160 Single AC/DC Power Supply Docking Station w/ Manual
Compatibility	AN/PRC 160
Input Voltage	85-260 VAC (47-63 Hz) • 20-33 VDC
Output Voltage	26.5 VDC regulated
Output Noise and Ripple	200mV Max
Output Protection	33.6 V
AUX Output	N/A
Battery Backup	Supported via Mil-Std DC input connector

PHYSICAL

Dimensions	8.38" H X 11.5" W X 11.59" D
Weight	9 lbs.
Color / Finish	OLIVE - 34094
LED Indicators	AC/DC power indicator Rx indicator

ENVIRONMENTAL

Operating Temp	-20° to 70° C
Storage Temp	-20° to 75° C
Airborne Moisture	95% Non-Condensing

OPTIONAL PTS PRODUCTS

for AS0160-HR-160

Component

Part Number

RAVEN - Rapid Deployment Folded Di-pole HF Antenna (150W)

ANT-PTS-000150-2-1



Component

Part Number

Fly Away HF Antenna Kit (Includes: 5m Mast and 150W HF Antenna)

ANT-PTS-305150-1-1

Component

Part Number

AS0160-HR-160 Deluxe Expeditionary Kit (E-Kit™)

Ekit.160.Deluxe

