

Power Supply Docking Station

AS0004-CNR-4T



- ♦ Low SWaP Design
- ♦ No assembly or training required
- ♦ Rapid installation in fixed and semi-fixed environments
- ♦ Integrated Speaker
- ♦ Uninterrupted AC/DC Switchover
- ♦ Simultaneously run two radios and two power amplifiers

GENERAL

PTS Part No	AS0004-CNR-4T
Description	CNR Dual AC/DC Power Supply Docking Station - Olive Drab w/ Manual
Compatibility	AN/PRC 2129 • RT-1523 • RT-1702
Input Voltage	85-260 VAC (47-63 Hz) • 20-33 VDC
Output Voltage	26.5 VDC regulated
Output Noise and Ripple	200mV Max
Output Protection	33.6 V
AUX Output	26.5 VDC regulated
Battery Backup	Supported via Mil-Std DC input connector

PHYSICAL

Dimensions	11.47"H X 14.0" W X 12.92" D
Weight	16.25 lbs.
Color / Finish	OLIVE - 34094
LED Indicators	AC/DC power indicator Rx indicator

ENVIRONMENTAL

Operating Temp	-20° to 70° C
Storage Temp	-20° to 75° C
Airborne Moisture	95% Non-Condensing

OPTIONAL PTS PRODUCTS

for AS0004-CNR-4T

Component	Part Number
-----------	-------------

7m Integrated Antenna Mast (IAM) -

ANT-RTL-307005-1-1



Component	Part Number
-----------	-------------

AS0004-CNR-4T Deluxe Expeditionary

Ekit.CNR4T.Deluxe