

# Power Supply Docking Station

AS0004-SR-4



- ◆ Low SWaP Design
- ◆ No assembly or training required
- ◆ Rapid installation in fixed and semi-fixed environments
- ◆ Integrated speaker

| GENERAL                        |  |
|--------------------------------|--|
| <b>PTS Part No</b>             | AS0004-SR-4  |
| <b>NSN</b>                     | 6130-01-618-9864   |
| <b>Description</b>             | SINGGARS 1523 ASIP Dual AC Only Power Supply Docking Station w/ Manual |
| <b>Compatibility</b>           | 2x of RT-1523  |
| <b>Input Voltage</b>           | 85-260 VAC (47-63 Hz) • 20-33 VDC                                      |
| <b>Output Voltage</b>          | 26.5 VDC regulated   |
| <b>Output Noise and Ripple</b> | 200mV Max  |
| <b>Output Protection</b>       | 33.6 V   |
| <b>AUX Output</b>              | N/A  |
| <b>Battery Backup</b>          | Supported via Mil-Std DC input connector                               |

| PHYSICAL              |                            |
|-----------------------|----------------------------|
| <b>Dimensions</b>     | 12.93"H x 17.5"W x 13.08"D |
| <b>Weight</b>         | 20 lbs                     |
| <b>Color / Finish</b> | OLIVE – 34094              |
| <b>LED Indicators</b> | Rx indicator               |

| ENVIRONMENTAL            |                    |
|--------------------------|--------------------|
| <b>Operating Temp</b>    | -20° to 70° C      |
| <b>Storage Temp</b>      | -20° to 75° C      |
| <b>Airborne Moisture</b> | 95% Non-Condensing |

# Optional PTS Products

for AS0004-SR-4

| Component                         | Part Number        |
|-----------------------------------|--------------------|
| 10m 4" mast/RolaCage system black | RLC-RTL-410002-3-1 |



| Component  | Part Number        |
|--|--------------------|
| 7m Integrated Antenna Mast (IAM) -<br>(Dual Band: 30-88 & 225-512 MHz) | ANT-PTS-307005-1-1 |