

Power Supply Docking Station

AS0117-HR-117G/152



- ◆ Low SWaP Design
- ◆ No assembly or training required
- ◆ Rapid installation in fixed and semi-fixed environments
- ◆ Integrated speaker
- ◆ Uninterrupted AC/DC switchover

GENERAL

PTS Part No	AS0117-HR-117G/152
Description	Harris 117G/152 Dual AC/DC Power Supply Docking Station w/ Manual (Vehicle Amplifier Required for Both Sides **GFE**)
Compatibility	RF 300M-V-150 • RF300M-V250 • RF300M-V255 • AN/VRC-110
Input Voltage	85-260 VAC (47-63 Hz) • 20-33 VDC
Output Voltage	26.5 VDC regulated
Output Noise and Ripple	200mV Max
Output Protection	33.6 V
AUX Output	N/A
Battery Backup	Supported via Mil-Std DC input connector

GENERAL

Dimensions	9.43"H x 17.5"W x 13.96"D
Weight	18 lbs.
Color / Finish	OLIVE – 34094
LED Indicators	AC/DC power indicator Rx indicator

ENVIRONMENTAL

Operating Temp	-20° to 70° C
Storage Temp	-20° to 75° C
Airborne Moisture	95% Non-Condensing



Expeditionary Communications

Optional PTS Products

AS0117-HR-117G/152

Component	Part Number
AS0117-HR-117G/152 Deluxe	Ekit.117G/152.Deluxe



Component	Part Number
System IAM 7m IAM-D (Dual Band: 30-88 & 225-	ANT-RTL-307005-1-1