

Power Supply Docking Station

AS0150-HR-5833/1523



- ◆ Low SWaP Design
- ◆ No assembly or training required
- ◆ Rapid installation in fixed and semi-fixed environments
- ◆ Integrated speaker
- ◆ Uninterrupted AC/DC switchover

GENERAL

PTS Part No	AS0150-HR-5833/1523
Description	Harris 150/1523 Dual AC/DC Power Supply Docking Station w/ Manual (Requires 5833 Amplifier for Harris Side **GFE**)
Compatibility	Side A: RF-5833-H Side B: RT-1523 • AM-7238B RFPA
Input Voltage	85-260 VAC (47-63 Hz) • 20-33 VDC
Output Voltage	26.5 VDC regulated
Output Noise and Ripple	200mV Max
Output Protection	33.6 V
AUX Output	26.5 VDC regulated
Battery Backup	Supported via Mil-Std DC input connector

GENERAL

Dimensions	11.77"H x 20.5"W x 13.09"D
Weight	21 lbs.
Color / Finish	OLIVE – 34094
LED Indicators	AC/DC power indicator Rx indicator

ENVIRONMENTAL

Operating Temp	-20° to 70° C
Storage Temp	-20° to 75° C
Airborne Moisture	95% Non-Condensing

Optional PTS Products

AS0150-HR-5833/1523

Component

Part Number

RAVEN - Rapid Deployment Folded Di-pole HF

ANT-PTS-000150-2-1



Component

Part Number

System IAM 7m IAM-D (Dual Band: 30-88 & 225-

ANT-RTL-307005-1-1